Product information DOSING EQUIPMENT



As easy as it gets - Installation, handling and operation.



dinodos EASY, capacity 0.2 - 4.5 l/h, Peristaltic dosing pump in wall mounting case, Hose connector 6/4mm Art. no.: 0220-270-00

Brief description

Description

Technical data

Use

Accessories

Spare parts

The dinodos EASY peristaltic pump is a high-quality, microprocessor-controlled peristaltic dosage pump for a precise dosage of liquid media and chemicals used in pool water treatment.

Microprocessor-controlled peristaltic dosage pump for an automatic addition of any kind of liquid media. With gear motor, ball bearing rotor axis and infinitely variable digital speed control. Continuous operation with an applied mains voltage of 230V.

The pump has a delivery rate of 4.5 l/h at a maximum counter-pressure of 1.5 bar. The delivery rate is adjustable via the speed control and by means of different pump hose sizes. With integrated dosage pump hose and hose connector DN 4 (4 mm).

Mains voltage:

Power consumption max.:

Protection class:

Dimensions housing (w x h x d):

Weight of pump:

Permissible ambient temperature:

Drive: Pump hose:

Capacity max.:

Suction lift max.:

Outdoor pool/Indoor pool

Operation:

230 V +/-10 %, 50/60 Hz

approx. 5 VA

IP 65

approx. 135 x 65 x 85 mm

approx. 0.6 kg +10 to +50 oC Gear motor

compl. with connection pieces for suction line DN4

approx. 0.25 - 4.5 l/h (infinitely adjustable), at a

counterpressure of max. 1.5 bar

1.80 m

Capacity adjustable via potentiometer

0204-025-00

Pump hose set incl. hose connector

0284-096-00 Suction line with float switch

0204-027-00 Rotor cover yellow 40 mm

Product information DOSING EQUIPMENT



Spare parts

0204-026-00Rotors with counter-pressure bearing and spring



0204-022-00 Pump hose set incl. hose connector

This may be interesting for you



0220-260-00 Easydos concept, capacity 5 - 200 ml/h



0220-266-00 Easydos concept, capacity 120 - 9000 ml/h



0220-264-00 Easydos concept, capacity 45 - 4500 ml/h

dinotec GmbH Water and Pool Technology

Spessartstrasse 7 63477 Maintal/Germany

Tel: +49(0)6109-6011-0
Fax: +49(0)6109-6011-90
Hotline: +49(0)6109-6011-72
E-Mail: mail@dinotec.de
Internet: www.dinotec.de

Subject to technical changes. Errors excepted.

Photo of item may be different.

Do you have any questions? Our hotline will be happy to help.

Status: 12.01.18